


# ChimneyFLEXible Liner

Flexible Stainless Steel Liner  
For Relining Masonry Chimney  
Listed to UL 1777 & ULC S635

# S.S. 316 Flexible Liner



Use for relining a masonry chimney.  
 Use for wood, gas, wood pellet, oil.  
 Applications: Fireplace inserts, furnaces, boilers and water heaters  
 Single ply .005" 316 Stainless Steel  
 10 Hills & Valleys for easy flexing.  
 Quadralock technology - Liner will never come apart  
 Liner also available in 9"-16"



A	B
3"	3.25"
4"	4.25"
5"	5.25"
5.5"	5.75"
5.75"	6"
6"	6.25"
7"	7.25"
8"	8.25"

DIAMETER	20'	25'	30'	35'	40'	45'	50'
3"	SSLI0320	SSLI0325	SSLI0330	SSLI0335	SSLI0340	SSLI0345	SSLI0350
4"	SSLI0420	SSLI0425	SSLI0430	SSLI0435	SSLI0440	SSLI0445	SSLI0450
5"	SSLI0520	SSLI0525	SSLI0530	SSLI0535	SSLI0540	SSLI0545	SSLI0550
5.5"	SSLI05.520	SSLI05.525	SSLI05.530	SSLI05.535	SSLI05.540	SSLI05.545	SSLI05.550
6" DD	SSLI0620	SSLI0625	SSLI0630	SSLI0635	SSLI0640	SSLI0645	SSLI0650
6" REG	SSLI06R20	SSLI06R25	SSLI06R30	SSLI06R35	SSLI06R40	SSLI06R45	SSLI06R50
7"	SSLI0720	SSLI0725	SSLI0730	SSLI0735	SSLI0740	SSLI0745	SSLI0750
8"	SSLI0820	SSLI0825	SSLI0830	SSLI0835	SSLI0840	SSLI0845	SSLI0850